



Effective Date: May 10, 2016

Product #(s) – 62304

Safety Data Sheet

For Emergency Call:
CHEM-TEL (800) 255-3924 24 Hour Assistance

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: PolyGuard Muriatic Acid

CAS Number: 7647-01-0 / 7732-18-5

Recommended Uses: Concrete Etching (Hydrochloric Acid, 31.45% (20° Baume))

Company Identification

Manufacturer's Name: ZECOL PRODUCTS COMPANY

Address: 4635 Willow Drive, Medina, MN 55340

Telephone – General Information: (763) 478-3438

2. HAZARDS IDENTIFICATION

Hazard Classes: Corrosive to Metals Category 1
Skin Corrosion/Irritation Category 1B
Acute (short-term) Aquatic Hazard Category 1

Signal Word: Danger

Hazard Statements:

H290 May be corrosive to metals.
H314 Causes severe skin burns and eye damage.
H335 May cause respiratory irritation.

Precautionary Statements:

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children,
P103 Read label before use.
P210 Keep away from heat.
P234 Keep only in original container.
P260 Do not breathe dusts or mists.
P264 Wash thoroughly after handling.
P271 Use outdoors or in a well-ventilated area.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P306 + P360 IF ON CLOTHING: Rinse immediately contaminated clothing and skin with plenty of water before removing clothes.

Product #(s) – 62304

P310	Immediately call a POISON CENTER/doctor.
P363	Wash contaminated clothing before reuse.
P390	Absorb spillage to prevent material damage.
P391	Collect spillage.
P406	Store in corrosive resistant container with a resistant inner liner,
P501	Dispose of contents/container to a specialized waste disposal plant in accordance with local/regional regulations.

Hazard Pictograms:



3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	Typical Weight Percentage	CAS Number
Hydrogen Chloride	31.45%	7647-01-0
Water	68.55%	7732-18-5

4. FIRST AID

Eyes: Immediately move victim away from exposure and into fresh air. If irritation or redness develops, flush eyes with clean water and seek immediate medical attention. For direct contact, remove contact lenses if present and easy to do so. Immediately hold eyelids apart and flush the affected eye(s) with clean water for at least 30 minutes. Seek immediate medical attention.

Skin: Immediately flush affected area(s) with large amounts of water while removing contaminated shoes, clothing and constrictive jewelry. If skin surface is damaged, apply a clean dressing and seek immediate medical attention. If skin surface is not damaged, cleanse the affected area(s) thoroughly by washing with mild soap and water. If irritation or redness develops, seek immediate medical attention.

Inhalation: Immediately move victim away from source of exposure and into fresh air. If respiratory symptoms or other symptoms of exposure develop, seek immediate medical attention. If breathing difficulties develop, oxygen should be administered by qualified personnel. Seek immediate medical attention.

Ingestion: ***Do NOT induce vomiting. Corrosive Material. Acid Burns.*** If victim has any breathing difficulties, call for emergency help immediately. If victim is conscious and alert, immediately rinse mouth with water and dilute the ingested material by giving one glass of milk or water to drink; ½ glass to children under 5. Never give anything by mouth to an unconscious person. Call a physician or POISON CENTER. If possible, do not leave victim unattended.

Note to Physician: This material is corrosive and may cause acid burns including gastroesophageal, gastric or pyloric structures and stenosis. Severe (3rd degree) acid burns to the esophagus have been associated with an increased risk of esophageal cancer.



Effective Date: May 10, 2016

Product #(s) – 62304

Medical Conditions: Conditions which may be aggravated by exposure include skin and respiratory disorders.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media: Water or water spray. Water spray is recommended to cool or protect exposed materials or structures. Neutralize with soda ash or slaked lime.

Specific Hazards: Contact with common metals can generate hydrogen, which can form flammable mixtures with air. If container is not properly cooled, it can explode in the heat of a fire.

Hazardous Combustion Products: May decompose upon heating to produce corrosive and/or toxic fumes.

Special Firefighting Procedures: For fires beyond the initial stage, emergency responders in the immediate hazard area should wear bunker gear. When the potential chemical hazard is unknown, in enclosed or confined spaces, or when explicitly required by DOT, a self-contained breathing apparatus should be worn. In addition, wear other appropriate protective equipment as conditions warrant (see Section 8). Isolate immediate hazard area and keep unauthorized personnel out. Cool equipment exposed to fire with water, if it can be done with minimal risk. Clean-up under expert supervision is advised.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: Isolate hazardous area and keep unauthorized personnel out. Clean-up under expert supervision is advised. Neutralize spilled material with alkaline materials (soda ash, lime). Wear appropriate protective equipment including respiratory protection as conditions warrant (see Section 8). See Sections 2 and 7 for additional information on hazards and precautionary measures.

Environmental Precautions: Stop spill/release if it can be done with minimal risk. Prevent spilled material from entering sewers, storm drains, other unauthorized treatment drainage systems, and natural waterways.

Methods for Containment and Clean-Up: Notify relevant authorities in accordance with all applicable regulations. Immediate cleanup of any spill is recommended. Dike far ahead of spill for later recovery or disposal. Absorb spill with inert material such as sand, earth or other non-combustible material, and place in suitable container for disposal. In case of soil contamination, remove contaminated soil for remediation or disposal, in accordance with local regulations.

7. HANDLING AND STORAGE

Precautions for Safe Handling: Wear protective gloves/clothing and eye/face protection. Wash thoroughly after handling. Use good personal hygiene practices and wear appropriate personal protective equipment (see Section 8). Do not wear contaminated clothing or shoes. Use good personal hygiene practice.

Conditions for Safe Storage: Keep container(s) tightly closed. Store in cool, dry, ventilated area with acid resistant floors and good drainage. Store only in approved containers. Protect from



Effective Date: May 10, 2016

Product #(s) – 62304

physical damage. Keep out of sunlight and direct heat and water. Keep away from any incompatible materials (see Section 10).

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Component	ACGIH TLV	ACGIH CEIL	OSHA PEL	OSHA CEIL
Hydrogen Chloride	---	2 ppm	---	5 ppm

Engineering Controls: If current ventilation practices are not adequate to maintain airborne concentrations below the established exposure limits, additional ventilation or exhaust systems may be required.

Specific Personal Protective Equipment

Eye/Face Protection: Wear a face shield along with goggles when working with corrosive, highly irritating or toxic substances. The use of eye protection that meets or exceeds ANSI Z.87.1 is recommended to protect against potential eye contact, irritation or injury

Skin: The use of gloves impervious to the specific material handled is advised to prevent skin contact. Users should check with manufacturers to confirm the breakthrough performance of their products. Depending on exposure and use conditions, additional protection may be necessary to prevent skin contact including use of items such as chemical resistant boots, aprons, arm covers, hoods, coveralls or encapsulated suits. Suggested protective materials: Neoprene or rubber.

Respiratory Protection: Wear a full face positive pressure air supplied respirator with an acid gas cartridge in situations where there may be potential for exceeding airborne exposure limits (see exposure guidelines). A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

Use a positive pressure air supplied respirator if there is potential for uncontrolled release, exposure levels are unknown, or any other circumstances where air-purifying respirators may not provide adequate protection.

Other Protective Equipment: Eye wash and quick-drench shower facilities should be available in the work area. Thoroughly clean shoes and wash contaminated clothing before reuse. It is recommended that impervious clothing be worn when skin contact is possible.

Suggestions provided in this section for exposure control and specific types of protective equipment are based on readily available information. Users should consult with the specific manufacturer to confirm the performance of their protective equipment. Specific situations may require consultation with industrial hygiene, safety, or engineering professionals.

9. PHYSICAL AND CHEMICAL PROPERTIES (approximate values based on propylene glycol)

Appearance: Clear, colorless liquid

Odor: Pungent, acrid

Odor threshold: No data



Effective Date: May 10, 2016

Product #(s) – 62304

pH: <1
Melting/Freezing Point: No data
Boiling point (at 1 atm): 82.2-104.4°C / 180-220 °F
Flash Point: Non-flammable
Auto-Ignition Temperature: Non-flammable
Evaporation rate (butyl acetate = 1): <1
Flammability (solid, gas): Not applicable
Explosive Limits: Non-flammable
Vapor Pressure: 35 mmg @ 86 °F
Vapor Density (air = 1): 1.27
Specific gravity (H₂O = 1): 1.155-1.162
Solubility in water: Soluble
Partition Coefficient: No data
Decomposition Temperature: No data
Viscosity: No data

10. STABILITY AND REACTIVITY

Stability (thermal, light, etc.): Stable under normal conditions of storage and handling.

Conditions to Avoid: Avoid heat and direct sunlight.

Incompatibility (materials to avoid): Highly reactive with oxidizing agents, strong bases, metals, metal oxides, hydroxides, amines, carbonates and alkaline materials. Incompatible with cyanide, sulfides, sulfites and formaldehyde.

Hazardous Decomposition Products: When heated to decomposition, emits toxic hydrogen chloride fumes and will react with water of steam to produce hot and toxic, corrosive fumes. Thermal decomposition in the presence of oxidizing materials produces toxic chlorine fumes and explosive hydrogen gas.

Hazardous Polymerization: Will not occur.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity:

Product/Ingredient Name	Result	Species	Dose
Hydrogen Chloride	LC50 Inhalation	Rat	45.6 mg/l (30 min.)

Skin Corrosion/Irritation: Corrosive. Contact may cause severe irritation, skin burns and permanent skin damage.

Serious Eye Damage/Irritation: Corrosive. Contact may cause severe irritation, eye burns and permanent eye damage

Signs and Symptoms: Can causes severe irritation of nose, throat and digestive tract, nausea, vomiting, abdominal pain, breathing difficulties, hypotension, pneumonitis and pulmonary edema

Skin Sensitization: None reported



Effective Date: May 10, 2016

Product #(s) – 62304

Respiratory Sensitization: No data found.

Germ Cell Mutagenicity: There is insufficient information available to conclude that this material is mutagenic

Carcinogenicity: There is insufficient information available to conclude that this material is carcinogenic. It is not listed by NTP, IARC or OSHA.

Reproductive Toxicity: No data found.

Specific Target Organ Toxicity (Single Exposure): None reported.

Specific Target Organ Toxicity (Repeated Exposure): There is insufficient information available to conclude that this material causes target organ toxicity.

12. ECOLOGICAL INFORMATION

Toxicity: High acidity may pose potential hazard to plant and marine life.

Other Adverse Effects: None known

13. DISPOSAL CONSIDERATIONS

The generator of a waste is always responsible for making proper hazardous waste determinations and needs to consider state and local requirements in addition to federal regulations.

Recycle wherever possible. Large volumes may be suitable for re-distillation or, if contaminated, incinerated. Can be disposed of in a sewage treatment facility.

This material, if discarded as produced would meet the criteria of a characteristic hazardous waste as defined by 40CFR 261 and would have the characteristic of corrosivity (D002). Use which results in chemical or physical change of this material could subject it to additional regulation as a hazardous waste.

14. TRANSPORT INFORMATION

DOT/TDG Proper Shipping Name: Hydrochloric Acid

DOT/TDG Identification Number: UN1789

DOT Hazard Class: 8 / **TDG Hazard Class:** 8

DOT/TDG Packing Group: II

ERG Guide Number: 157

Marine Pollutant: No

15. REGULATORY INFORMATION

TSCA: Components are listed on the TSCA inventory.

DSL: Components are listed on the DSL inventory.



Effective Date: May 10, 2016

Product #(s) – 62304

OSHA (Occupational Safety and Health Administration): This material is considered to be hazardous as defined by the OSHA Hazard Communication Standard.

This material has not been identified as a carcinogen by NTP, IARC or OSHA

CERCLA/SARA – Section 302 Extremely Hazardous Substances and TPQ (in pounds): This material contains chemicals subject to the reporting requirements of SARA 302 and 40 CFR 355 Appendix A and B.

Component	Concentration	TPQ
Hydrochloric Acid (gas only)	31.45%	500

EPA (CERCLA) Reportable Quantity (in pounds): This material contains the following chemicals subject to the reporting requirements of 40 CFR 302.4:

Component	Concentration	RQ
Hydrochloric Acid	31.45%	5000

CERCLA/SARA - Sections 311/312 (Title III Hazard Categories):

Acute: Yes Chronic: No Fire: No Reactivity: Yes

CERCLA/SARA – Section 313 and 40 CFR 372: This material contains chemicals subject to the reporting requirements of SARA 313 and SARA Title III and 40 CFR:

Component	Concentration	De minimis
Hydrochloric acid (acid aerosols including mists, vapors, gas, fog, and other airborne forms of any particle size)	31.45%	1%

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material does NOT contain detectable chemicals known to the State of California to cause cancer and/or reproductive toxicity.

Canada:

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the Regulations.

WHMIS Hazard Class: E (corrosive)

16. OTHER INFORMATION

Issue Date: May 10, 2016
Previous Issue Date: April 27, 2014
Change: Fixed typo in Sec. 14 ID No.

DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES

The information in this document is believed to be correct as of the date issued. **HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR**



Effective Date: May 10, 2016

Product #(s) – 62304

COMPLETENESS OF THIS INFORMATION, THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE. This information and product are furnished on the condition that the person receiving them shall make his own determination as to the suitability of the product for this particular purpose and on the condition that he assumes the risk of his use thereof.